# Sysocmgr

Installs a limited set of optional components.

## Syntax

**sysocmgr**[**.exe**] **/i:***InfFile***.inf** [**/u:***AnswerFilePathAndName* [**/q**][**/w**]] [**/r**][**/z**][**/n**][**/f**][**/c**][**/x**] [/

## Parameters

**/i:***InfFile***.inf**

Required. Designates the *InfFile***.inf** that you specify as the master .inf file.

**/u:***AnswerFilePathAndName*

Specifies the path and file name of an optional answer file that contains parameters for unattended installation.

**/q**

Runs the unattended installation without a user interface. You cannot use **/q** without **/u**.

**/w**

Prompts the user before rebooting, only if reboot is required. You cannot use **/w** without **/u**.

**/r**

Suppresses reboot. If reboot is not necessary, this command-line option has no effect.

**/z**

Indicates that the arguments that follow are not optional component arguments and they should be passed to the components.

**/n**

Forces the master .inf to be treated as new.

**/f**

Indicates that all component installation states should be initialized as if their installers had never been run.

**/c**

Disallows cancellation during the final installation phase.

**/x**

Suppresses the initializing banner.

**/l**

Multi-language aware installation.

[**/?**] [**/h**] [*IncorrectSyntax*]

Displays help in a separate window, not at the command prompt.

## Remarks

- For examples of how to use sysocmgr, search the Microsoft Knowledge Base using the keyword **sysocmgr**.

- For an answer file example, see Unattended setup.

## Examples

The following example shows how you can use **sysocmgr**:

**sysocmgr.exe /i:sysoc.inf /u:unattend.txt**

## Formatting legend

| Format | Meaning |
| --- | --- |
| *Italic* | Information that the user must supply |
| **Bold** | Elements that the user must type exactly as shown |
| Ellipsis (...) | Parameter that can be repeated several times in a command line |
| Between brackets ([]) | Optional items |
| Between braces ({}); choices separated by pipe (\|). Example: {even\|odd} | Set of choices from which the user must choose only one |
| Courier font | Code or program output |

### Related Topics

[?] [Command-line reference A-Z](Command-line reference A-Z)
[?] [Command shell overview](Command shell overview)